

# FELCO 160L - Green

Pruning shear - Model for large hands

Made in Switzerland by FELCO, US: PATENT NO US D584,121 S, AU and CN: PATENTED













- > Reliable: incredibly light, hardwearing and comfortable handles mades of very high-resistance composite fibre / blade and anvil blade made of high-quality hardened steel / clean and precise cut / all parts suffering wear and tear are replaceable
- > Efficient: very easy, durable cutting adjustment
- > Ergonomic: hand and wrist protection are provided by the ideal shape of the handles / pleasant feel



### **RECOMMENDED FOR**

Our recommendation ( = Recommended, = Strongly recommended, = Best fit)

Viticulture

Arboriculture

Horticulture

Parks and Gardens

Nursery

Small hand

Average-sized hand

Large hand

Left-handed

# THE POINTS OF EXCELLENCE



#### Composite material handles

Glass fiber reinforced high-resistance polymers.



#### Angled cutting head

Inclined cutting head to reduce the risk of muscular-skeletal injuries and to maximise user comfort.



## **ACCESSORIES**









FELCO 902 Sharpening tool Sharpening stone

FELCO 903 Sharpening tool Sharpener

FELCO 910 Holster Leather - With belt loop and clip

FELCO 912
Holster
Leather - With belt clip



FELCO 980 Maintenance product Spray



FELCO 990 Maintenance product Grease



# **SPARE PARTS**



FELCO	REF.	Designation	Composition	UCC Barcode
•	5/3	Blade	1x 5/3	7 83929 40002 0
Vo jo	160L/4	Anvil-blade with screws and nuts	1x 160L/4 + 2x 160/6 + 2x 160/7	7 83929 40146 1
	2/91	Kit	2x 2/11	7 83929 40018 1
<b>(a)</b>	160/94	Kit	1x 160/9 + 1x 160/8	7 83929 40095 2
	160L/1	Handle without blade	1x 160L/1 + 1x 5/5B	7 83929 40144 7
	160L/2	Handle without anvil- blade	1x 160L/2	7 83929 40145 4
=	5/5B	Rivet for blade	1x 5/5B	7 83929 40211 6
0	160/6	Screw for anvil-blade	1x 160/6	7 83929 40140 9
•	160/7	Nut for anvil-blade	1x 160/7	7 83929 40141 6



	160/8	Bolt	1x 160/8	7 83929 40142 3
	160/9	Nut	1x 160/9	7 83929 40143 0
	2/11	White spring	1x 2/11	7 83929 40152 2



### **MAINTENANCE**



#### Cleaning

It is advisable to clean your tool after each use.

If your tool is particularly dirty or subject to rusting after exposure to moisture, do not delay cleaning.



### Oiling

After cleaning, it is advisable to oil the tool so as to protect it from corrosion. The oil will also unjam the tool.



#### Sharpening

It is advisable to sharpen your tool at least once a day, but if you feel that your tool is not cutting as well as usual, sharpen it right away!



#### Dismantling

It is advisable to dismantle your tool on a regular basis, but at the very latest when it appears to be jammed.



## **PARTS REPLACEMENT**



### Changing the blade

When the blade and the anvil-blade no longer cross, or when the blade is badly damaged, it is advisable to change it.

Regulate the working of the blade and anvil-blade by adjusting the tightening of the nut. The blade should rub against the anvil-blade over 2/3 of its length.



### Changing the anvil-blade

When the blade and anvil-blade no longer cross and the anvil-blade is badly damaged, it is advisable to change it.